

### Datasheet

#### Automatic Duplex, Windows® & Mac® Laser Printer

Up to 20 / 21 pages per minute monochrome printing

#### **Automatic Duplex Printing**

Up to **HQ1200** Printing

**16MB** as standard, expandable up to **144MB** total memory

Hi-Speed USB 2.0 and Parallel IEEE1284 ports as standard

Optional Network: 10/100BaseTX

PCL<sup>®</sup>6 & BR-Script 3 (Adobe™ PostScript<sup>®</sup> 3 language emulation) Epson FX-850, IBM Proprinter XL

Wide Compatibility: Windows®, Mac®, Linux & DOS

133MHz processor

Up to 250 sheets standard input capacity and optional 250 sheet tray


Plus a 50 sheet multipurpose tray -

to manage plain, recycled and bond paper, envelopes, labels and transparencies

First print out in under 10 seconds

Convenient Job-Cancel button

**High yield**, 6700 pages\* and **standard yield**, 3500 pages\* toner, 20,000 drum pages





### **Features**

**Engine** 

Electrophotographic Monochrome Technology Print Speed

Α4 20 pages per minute Letter 21 pages per minute

9 sides per minute (4.5 sheets per minute) Duplex

First Print Time Less than 10 seconds

Resolution

Windows® 95/98/ HQ1200 High Quality Me/NT®4.0/2000/XP Normal 600 x 600dpi

Draft 300 x 300dpi

Mac® OS 8.6-9.2/ High Quality HQ1200 OSX 10.1-10.2 Normal 600 x 600dpi

Draft 300 x 300dpi

High Quality Linux HQ1200 Normal

600 x 600dpi Draft 300 x 300dpi

DOS 600 x 600dpi

Controller

Fujitsu SPARClite (133MHz)

Memory Standard 16 MB

Optional Expandable up to 144MB, using industry standard 1 DIMM (100 PIN) slot

Standard Hi-Speed USB 2.0 IEEE Parallel 1284

**Network Connectivity** Optional 10/100baseTX - see accessories

PCL®6 & BR-Script 3 (Adobe™ PostScript® 3 language emulation), Epson FX-850, IBM ProPrinter XL Resident Fonts

66 scaleable fonts, 12 bitmap fonts and 11 barcodes

BR-Script 3 66 scaleable fonts

**Software** 

Printer Driver Windows® PCL driver for Windows®95<sup>1</sup>98/Me/NT®4.0/2000 and XP

BR-Script3 driver for Windows®95/98/Me/NT®4.0/2000 and XP Macintosh® Brother laser driver for Mac® OS 8.6-9.2, OS X 10.1-10.2

BR-Script3 driver for Mac® OS 8.6-9.2, OS X 10.1-10.2

Linux GDI printer driver

BR-Script 3 printer driver

Utility Interactive help (on-screen guidelines using moving pictures)

**Printer Driver Functions** 

Page Layout N-up Printing Reduce up to 2,4,9,16, or 25 A4 pages into just one A4 page Enlarge one A4 page into a poster using 4,9,16 or 25 A4 pages Poster Printing †

Watermark Printing † Watermark your documents with predefined text or with your own user-defined messages

Others Automatic two-sided booklet printing, reduce an A4 32 page document into an A5 8 page booklet. **Booklet Printing** 

Quick Print Set-up † Allows users to quickly select print options in the driver Indicates the status of the printer onto a PC Status Monitor †

**Control Panel** 

LED 4 LED lights, Toner, Drum, Paper and a 3 colour Status LED Display

Buttons There are two buttons, Job Cancel and "Go".



### **Features**

Paper Handling

Standard Standard Trav: Paper Input\* 250 sheets

> Optional Lower Tray Total paper capacity of 550 sheets can be stored, if the optional lower tray is chosen

see accessories

Multi-purpose Tray: Standard 50 sheet multipurpose tray

Paper Output\*\* Standard Face Down: 150 sheets Face Up: 25 sheets

Duplex Standard Automatic two-sided prints

Media Specifications

Media Types This printer accepts the following media types

Standard Standard Tray: Plain paper, Bond paper, Recycled paper and Transparencies\*\*\* Optional Lower Tray: Plain paper, Bond paper, Recycled paper and Transparencies\*\*\*

Standard Multipurpose Tray: Plain paper, Bond paper, Recycled paper, Transparencies, Envelopes or Labels

Standard Duplex: Plain paper, Bond paper, Recycled paper

Media Weights This printer accepts the following media weights:

Standard Tray: Standard  $60 - 105g/m^2$ Lower Tray: Optional 60 - 105g/m<sup>2</sup> Standard Multipurpose Tray: 60 - 161g/m<sup>2</sup> Standard Duplex -60 – 105g/m<sup>2</sup>

Media Sizes This printer accepts the following media sizes:

Standard Standard Tray: Cut sheet: A4, Letter, B5(ISO), A5, B6(ISO), A6, Executive, Legal

Cut sheet: A4, Letter, B5 (ISO), A5, Executive, Legal Optional Lower Tray: Standard Multipurpose Tray: Custom: Width (69.9 - 215.9mm) x Length (116.0 x 406.4)

Supplies

TN-3030 Standard yield of 3,500 A4 or letter pages @ 5% coverage TN-3060 High yield of 6,700 A4 or Letter pages @ 5% coverage

DR-3000 20,000 A4 or letter pages (one page per job)

The frequency of replacement of consumables will vary depending on the complexity of the prints, the percentage of

coverage, paper size, page per job, and the type of media. For example, transparencies, glossy coated paper will

result in a shortened life of such supplies.

Accessories

Network Connection NC-2100p Fast Ethernet connection 10/100BaseTX

Paper Tray 250 sheet capacity lower tray

**Dimensions & Weights** 

(382mm width) x (401mm depth) x (252mm high) Dimensions

Weight

**Others** 

Noise Level

**Power Consumption** Printing Less than 460WH

Standby Less than 75WH Sleep Less than 5WH Printing Less than 50 dB Standby Less than 30 dB

Power Saving Ecology This enables the printer to consume less energy when not in use

Toner Saving This reduces the toner usage and helps to reduce the total cost of printer ownership.

A4 / Letter pages @ 5% coverage Calculated with 80g/m² paper

Up to 10 sheets . Windows® only



# Logistical Information

Reference	Description	EAN code	UPC code	Interleave	Carton dimensions (mm)			Carton Weight (Kg)	Country of origin
					W	D	Н		
HL5150D	Printer	4977766623537							China
NC-2100p	Network card								
LT-5000	Lower Tray	4977766607896							China
TN-3030	Std. Yield Toner	4977766623551							China
TN-3060	High Yield Toner	4977766623568							China
DR-3000	Drum Yield	4977766623575							China

Specifications correct as at 30/09/2003 and are subject to change. Datasheet prepared by BIE Marketing.