

PIXMA MP630



Fast, high-quality and feature-packed home printing for creative users

All-In-One with premium 1pl, 9600dpi* print engine for superior-quality photos and documents. Includes advanced media handling features for digital photographers, creatives and demanding home users.

The PIXMA MP630 is part of the PIXMA All-In-One Home print, copy and scan range. The PIXMA All-In-One Home range consists of: PIXMA MP980, **PIXMA MP630**, PIXMA MP620, PIXMA MP540, PIXMA MP480, PIXMA MP260, PIXMA MP240, PIXMA MP190 Embargo Date:26th August 2008Sales Start Date:OctoberTarget Market:Home users and digital
camera users

Key Features

- Premium 9600dpi print resolution and 1pl ink droplets*
- Photolab-quality 10x15cm prints in approximately 20 seconds*
- Single Ink tanks to minimise ink wastage
- ChromaLife100⁺ system for long-lasting, beautiful photos**
- Pre-load different paper types with two paper trays
- Intuitive operation with Easy-Scroll Wheel and large 6.2cm TFT display
- Advanced media handling with auto duplex printing and printing to DVD/CD
- High-resolution 4800dpi scanning for improved clarity
- Scan to memory card and USB stick for extra versatility

* See specifications

** See www.canon-europe.com/chromalife100

Product Name	Mercury Code	EAN Code	Recommended Retail Price
PIXMA MP630	2920B008AA	4960999579160	£159 / €206.36

What's in the box:

PIXMA MP630, Power cord, Printer Head, Consumables (PGI-520BK, CLI-521 Bk, CLI-521 C, CLI-521 M, CLI-521 Y), Multilingual set up guides, Setup software & User's manual CDs including MP Navigator EX and Easy-PhotoPrint EX, Media Brochure, Sample Media PP-201 10x15cm (3 sheets), MP-101 A4 for Head Alignment (2 sheets), Warranty sheet

Consumables	Mercury Code	EAN Code	Recommended retail price
PGI-520 Bk	2932B001AA	4960999577456	£8.99 / €11.99
CLI-521 Bk	2933B001AA	4960999577470	£7.99 / €10.99
CLI-521 C	2934B001AA	4960999577494	£7.99 / €10.99
CLI-521 M	2935B001AA	4960999577517	£7.99 / €10.99
CLI-521 Y	2936B001AA	4960999577531	£7.99 / €10.99

Note: Blister packs with and without security are available for each of the inks listed above

you can

PIXMA MP630

Technical Specifications

TYPE Available Functions	Print Scan & Copy. Premium Photo All-In-One with Easy- Scroll Wheel, 6.2cm colour TFT display, direct CD printing & duplex print/copy.	INTERFACE AND SOFTWARE Interface Type – PC	Hi-Speed USB (B Port), Bluetooth Ver2.0 maximum speed 1.44Mbps (Option, HCRP) (with optional Bluetooth Unit BU-30)
PRINTER FUNCTIONS Print Resolution Print Engine	Up to 9600 ¹ x 2400 dpi Inklet 5-ink with minimum 1 pl droplet size, FINE print head and ContrastPLUS	Interface Type - Mobile Phone / PDA	Bluetooth Ver2.0 maximum speed 1.44Mbps (Option, JPEG only, OPP, BIP) (with optional Bluetooth unit BU-30) Photo printing via PictBridge
Photo Lab Quality Speed Mono Print Speed	Borderless 10 x 15cm: Approx. 20 seconds (Standard) Up to 25ppm (Max.), 12.8ppm (Standard)	Supported Operating System	Windows Vista (32bit, 64bit) / Windows XP SP2 / Windows 2000 Professional SP4 Mac OS X v.10.3.9 - v.10.5
Colour Print Speed Ink Cartridge Configuration	Text & Graphics: Up to 21ppm (Max.), 11.2ppm (Standard) Single Ink technology - 5 separate ink tanks (PGI-520BK,	Operating System Requirements	Windows Internet Explorer 6.0 / CD-ROM drive / Display 1024x768
Black Ink Tank Life	CLI-521C, CLI-521M, CLI-521Y, CLI-521BK) Black: 350 pages (PGI-520BK), 1875 pages* (CLI-521BK) ² Black: 3160 photos* (PGI-520BK),	Software Included	Mac OS X / Safari /CD-ROM drive / Display 1024x768 Canon MP Navigator EX, Canon Easy-PhotoPrint EX, CD-LabelPrint
Colour Ink Tank Life	665 photos* (CLI-521BK) ³ * <i>Estimated Supplemental Yield</i> Cyan: 505 pages (CLI-521C), Magenta: 471 pages (CLI-521M), Yellow: 505 pages (CLI-521Y) ²	GENERAL FEATURES Dimensions (W x D x H)	450 × 368 × 176mm
Media Type	Cyan: 205 photos (CLI-521C), Magenta: 206 photos (CLI-521M), Yellow: 211 photos (CLI-521Y) ³ Plain Paper, Envelopes, Photo Paper Pro Platinum (PT-101), Photo Paper Pro II (PR-201), Photo Paper Plus	Number of language (LCD)	22 Languages selectable: Japanese, English, German, French, Italian, Spanish, Dutch, Portuguese, Norwegian, Swedish, Danish, Finnish, Russian, Czech,
	Glossy II (PP-201), Photo Paper Plus Semi-gloss (SG-201), Glossy Photo Paper "Everyday Use" (GP-501), Matte Photo Paper (MP-101), High Resolution Paper (HR-101N), T-shirt Transfer (TR-301), Photo Stickers	Temperature Range Humidity	Hungarian, Polish, Slovenian, Turkish, Simplified Chinese, Greek, Traditional Chinese, Korean Operating environment: 5° - 35° C Operating humidity: 10 - 90%RH (no condensation)
Media Input	(PS-101)Rear Tray: Max. 100 sheets Rear Tray: Max. 150 sheets Front Tray: Max. 150 sheets	Acoustic Noise Levels	Printing (when feeding from rear tray): Approx. 46.5 dB(A). When printing ISO/IIS-SCID N2 pattern bordered on A4 plain paper with the default settings
Media Size	DVD/CD Tray: 1 printable DVD or CD Rear Tray: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm, 20 x 25cm Cassette: A4, B5, A5, Letter	Weight Power Source Power Consumption	Approx. 8.8 kg AC 100-240V, 50/60Hz Standby: Approx. 2.1W (when scanning lamp is off) Off: 0.5W
Media Weight	Rear Tray: Plain paper: 64 to 105 g/m ² and supported Canon special media up to 300 g/m ² Cassette: Plain paper: 64 to 105 g/m ²	Copying: Approx. 16W ⁵ 1. Ink droplets can be placed with a minimum pitch of 1/9600 inch	
DVD/CD Printing Two Sided Printing	Available as standard Automatically selectable using plain paper in A4, B5,	printing. 3. Printing Canon standard pho	dance with ISO/IEC 24711. Values obtained by continuous tos continuously on 10x15cm Photo Paper Plus Glossy II
Borderless Printing Camera Interface and	A5 & Letter sizes Yes (A4, Letter, 20 x 25cm, 13 x 18cm, 10 x 15cm) Direct Print Port: Camera direct photo printing from	with default settings using Windows Vista printer driver in borderless printing mode and Windows Vista Home Premium Photo Gallery. Declared yield value determined based on Canon standard method referring to ISO/IEC 24711.	
Connectivity Card Direct Printing	PictBridge compliant digital cameras & camcorders CompactFlash, Microdrive, Memory Stick, Memory Stick Pro, Memory Stick Duo, Memory Stick PRO Duo,	 Using recommended adapter - not supplied When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings. 	
	SD Memory Card, SDHC Memory Card, MultiMedia Card (Ver4.1), and MultiMedia Card Plus (Ver4.1). xD-PictureCard ⁺ , xD-PictureCard Type M ⁺ , XD-PictureCard Type H ⁴ , Memory Stick Micro ⁴ , RS-MMC ⁴ , mini SD Card ⁴ , micro SD ⁴ , mini SDHC Card ⁴ and micro SDHC ⁴ .	All specifications subject to change without notice. Borderless 10x15cm photo lab quality print speed based on Standard driver setting using ISO/IIS-SCID N2 on Canon Photo Paper Plus Glossy II media. PPM print speed is based on the highest speed mode setting using Canon standard	
SCANNER FUNCTIONS		printer and may vary depend	t speed measured as soon as first page begins to feed into ling upon a number of factors. Print speed does not take
Scanner Type Scanner Resolution Optical	Flatbed CIS colour scanner Up to 4800 x 9600dpi		Canon standard pattern in fast mode setting using plain
Scanner Resolution Digital		paper. Copy speed may vary complexity and copy mode.	depending on a number of factors including document
Colour Scanning Depth Halftone/Greyscale	48 / 24 bit (RGB each 16 / 8 bit) 16 / 8 bit	Ink yield may vary depending	g on texts/photos printed, applications software used,
Compatibility	TWAIN / WIA (Windows XP / Windows Vista)	www.canon-europe.com/ink	r used. For yield information see / <u>yield</u>
Effective Scanning Width OCR Bundle	A4/LTR Yes (MP Navigator EX)	Microsoft, Windows and the Microsoft Corporation in the	s are trademarks of their respective companies. Windows logo are trademarks, or registered trademarks of United States and/or other countries.
COPIER FUNCTIONS		For more information on Chr www.canon-europe.com/chr	
Colour/Photo Copy	Yes		
Copy Speed Mono Copy Speed Colour	Up to 24cpm Up to 19cpm		
Multiple Copy	max.99 copies		
Zoom	25 - 400% in 1% increments and preset ratios		