

Be more productive
with easy-to-use, Wi-Fi*
and network* ready,
mono laser 4-in-1**

i-SENSYS
MF4730

i-SENSYS
MF4750

i-SENSYS
MF4780w

you can



Network* and Wi-Fi* ready, easy-to-use, compact mono laser multifunctional.

Wi-Fi* and network* ready, this mono laser multifunctional is freely accessed from around the home or office. Quick, easy-to-use and energy efficient, it is the ideal productivity booster.

Key features

- Compact, space-saving multifunctional printer, copier, scanner and fax**
- Wi-Fi* for wireless access around the home or office
- Quick 23ppm mono laser print and copy speed
- Simple operation with intuitive tilting control panel and large LCD screen
- Productivity-boosting, one-touch solution keys for managing scanning and copying workflows
- Built-in networking* to share printing, scanning and faxing
- Quick First-Print offers fastest recovery time from sleep mode
- 35-sheet Automatic Document Feeder
- Save energy and cost with class-leading energy efficiency

What's in the box

Main unit, starter cartridge 728, power cord, telephone line cable, handset clamp, starter guide, wireless set-up guide* and warranty card - with user software and manual CDs.

Dimensions (W x D x H)

390mm x 439mm x 360mm

Supported OS

Windows 7 / XP / Vista / Server 2003* / Server 2008* / Server 2008 R2*

Mac OS Version 10.4.9 and up (Web distribution only)

Linux (Web distribution only)



PRINT



COPY



FAX**



SCAN

*MF4780w only **MF4750 and MF4780w only.

Canon

i-SENSYS
MF4730

i-SENSYS
MF4750

i-SENSYS
MF4780w



- 1 Flatbed ADF
- 2 Tilting control panel
- 3 250-sheet tray
- 4 Cartridge 728



Specifications:

Machine type Available functions	Mono Laser All-in-One Print, Copy, Scan and Fax ¹
PRINTER Print speed Printing method Print quality Print resolution First Print Out Time Printer languages Print margins Toner saver mode	Up to 23ppm (A4) Monochrome laser beam printing Up to 1200 x 600 dpi with Automatic Image Refinement 600 x 600 dpi 6 seconds UFRII-LT 5mm – top and bottom, 5mm – left and right Yes
COPIER Copy speed First Copy Output Time (FCOT) Copy resolution Copy modes Multiple copy Reduction / Enlargement Toner saver mode Other features	Up to 23ppm (A4) Approx. 9 seconds or less Up to 600 x 600 dpi Text, Text/Photo, Text/Photo+, Photo Up to 99 copies 25-400% in 1% increments Yes Memory sort, 2 on 1, 4 on 1, ID Card Copy
SCANNER Type Scan resolution Colour scanning depth Greyscales Compatibility Max. scan width	Colour Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi 24 bit / 24 bit (input / output) 256 levels TWAIN, WIA 216mm
FAX¹ Modem speed Receive mode Fax resolution Fax memory Speed dials Group dials / destinations Sequential broadcast Memory backup Other features Fax only applies to MF4750dn and MF4780w	Super G3 33.6kbps Fax Only, Manual, Answering, Fax / Tel Auto SW Standard: 200 x 100 dpi Fine: 200 x 200 dpi Photo: 200 x 200 dpi Super fine: 200 x 400 dpi Up to 256 pages ² Max. 103 (including 3 one-touch dials) Max. 102 destinations Max. 113 locations Unlimited Dual Access, Remote RX, PC Fax (sending only), Fax Forwarding, DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports
MEDIA HANDLING Scanner type Paper input (Standard) Paper output Media types Media sizes Manual feed slot: ADF: Media weights	Flatbed and Automatic Document Feeder (ADF) 250-sheet tray, 1-sheet manual feed slot, 35-sheet ADF 100-sheet Plain paper, Heavy paper, Recycled paper, Transparency, Label, Envelope Tray: A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard, Envelope: COM10, Monarch, C5, DL, Custom sizes: Min. 76.2 x 210mm to Max. 216 x 356mm Manual feed slot: A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard, Envelope: COM10, Monarch, C5, DL, Custom sizes: Min. 76.2 x 127mm to Max. 216 x 356mm ADF: A4, B5, A5, B6, LTR, LGL Min. 105 x 148mm to Max. 356 x 216mm Tray: 60 to 163g/m ² Manual feed slot: 60 to 163g/m ²

INTERFACE & SOFTWARE Interface type Operating System compatibility Software and printer management	USB 2.0 Hi-speed, 10BASE-T / 100BASE-TX ³ , Wi-Fi 802.11b/g/n ³ Windows 7 / XP / Vista / Server 2003 ^{3,4} / Server 2008 ^{3,4} / Server 2008 R2 ^{3,4} / Mac OS X Version 10.4.9 and up ⁵ / Linux ^{5,6} Remote User Interface (RUI) ³ , Printer driver, Fax driver ¹ , Scanner driver, MF Toolbox, AddressBookTool ¹ , Presto! PageManager, SSID Tool ³
GENERAL FEATURES Duty cycle Warm-up Time Memory Control panel Dimensions with trays (W x D x H) Installation space (W x D x H) Weight Operating environment Power Source Power Consumption Noise Levels	Max. 10,000 pages per month Approx. 13.5 seconds from power on 128MB 5 lines BW LCD 390mm x 439mm x 360mm 426mm x 555mm x 623mm 11.9kg Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) 220-240V (±10%), 50/60Hz (±2Hz) Maximum: Approx. less than 1320W Active: Approx. less than 560W Stand by mode: Approx. 5W Sleep mode: Approx. 1.4W ⁷ Typical Electricity Consumption (TEC): 0.7kWh/week Sound Pressure: Active: 50dB(A) or less Standby: Inaudible
CONSUMABLES Cartridges	Cartridge 728 (2,100 pages ⁸) ⁸
ACCESSORIES / OPTIONS Items	TELEPHONE KIT 6 ¹
Standard disclaimers. All specifications subject to change without notice. 1) MF4750 and MF4780w only 2) Based on ITU-T Standard Chart No. 1 3) MF4780w only 4) Network scanning not supported 5) Web distribution only 6) Linux support printing only 7) When in wireless mode, consumption will be 2.4W 8) Ships with 1,000 pages starter cartridge 9) Based on ISO/IEC 19752	



Canon

Canon Electronics Inc
canon.com

Canon Europe
canon-europe.com

European Edition 0000
© Canon Europa N.V.,
2012 (0000)