

bizhub C3850

- Colour A4 multifunctional

✓ Functionality



– Colour – Black & white



ColourBlack & whitePCL/PSLocal/Network

- USB



- Colour - Black & white - Scan-to-eMail
- Scan-to-HDDScan-to-USB
- Scan-to-USBScan-to-WebDAV
- Scan-to-SMBScan-to-FTP
- TWAIN Network



– Super G3 Fax – PC-Fax – i-Fax

Favina












Technology

Emperon™ – print controller	Easily compatible to users and IT environments thanks to Konica Minolta unified print technology	V
Simitri® HD – polymerised toner	Pays off to budget and green footprint by high quality and low environmental impact	V
OpenAPI – solution platform	Enable efficient workflows throughout your MFP fleet by server-based applications	V
i-Option – special feature	Increase the scope of MFP functionality from basic to advanced depending on your needs	V
CSRC – remote service	Keep productivity up by online device and consumable monitoring of the Konica Minolta service	V
IWS – panel customisation	Improved user-device interaction and productivity by full MFP panel customisation to your needs	X

Option diagram



Finishing options





Corner stapling (off-line)

Duplex

Descriptions

bizhub C3850	A4 multifunctional with 38 ppm b/w and colour.
	Standard Emperon™ print controller with PCL, PostScript
	and XPS support. Paper capacity of 550 sheets and
	100-sheet manual bypass. Automatic duplex document
	feeder and duplex unit standard. 1 GB memory, 320 GB
	hard disk and Gigabit Ethernet standard.
PF-P13 Paper tray	A4, 500 sheets, 60-90 gsm
DK-P03 Copier desk	Provides storage space for print media, etc.
FS-P03 Off-line stapler	20-sheet corner stapling
KP-101 10-Key pad	For use instead of touchscreen

WT-P02 Working table	Off-line stapler placement, etc.
FK-512 Fax board	Super G3 fax, digital fax functionality
MK-738 Fax mount kit	Installation kit for fax board
ID card reader	Various ID card technologies
MK-P02 Mount kit	Installation kit for ID card reader
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-111 ThinPrint® client	Print data compression for reduced network impact
SX-BR-4600 Wireless LAN	Wireless LAN to network connector

Technical specifications

SYSTEM SPECIFICATIONS

System memory	1 GB (standard)
System hard disk	320 GB (standard)
Interface	10-Base-T/100-Base-TX/1,000-Base-T Ethernet; USB 2.0
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP; HTTPS
Frame types	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP
Automatic document	Up to 50 originals; A5-A4; 50-128 gsm; reverse automatic
feeder	document feeder
Printable paper size	A6-A4, customised paper sizes
Printable paper weight	60-210 gsm
Paper input capacity	Standard: 650 sheets
	Max.: 1,650 sheets
Tray 1	550 sheets, A6 – A4, 60 – 210 gsm
Tray 2 (optional)	500 sheets, A4, 60 – 90 gsm
Tray 3 (optional)	500 sheets, A4, 60 – 90 gsm
Manual bypass	100 sheets, A6-A4, custom sizes, 60-210 gsm
Automatic duplexing	A4; 60-210 gsm
Finishing modes	Staple (off-line)
(optional)	
Output capacity	Max.: 250 sheets
Stapling (optional)	Max.: 20 sheets (off-line stapling)
Copy/print volume	Rec.: 6,500 pages
(monthly)	Max.1: 120,000 pages
Toner lifetime	CMYK: 10,000 pages
Imaging unit lifetime	CMYK: 60,000 pages
Power consumption	220-240 V/50/60 Hz, Less than 1.7 kW
System dimensions	555 x 584 x 603 mm
(W x D x H)	
System weight	Approx. 47.6 kg

COPIER SPECIFICATIONS

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD polymerised toner
Copy/print speed A4	Up to 38 ppm
(mono/colour)	
Autoduplex speed A4	Up to 38 ppm
(mono/colour)	
1st copy out time	7.2 sec.
(mono/colour)	8.1 sec.
Warm-up time	Approx. 30 sec. ²
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-999
Original format	Max. A4
Magnification	25-400% in 0.1% steps; auto-zooming
Copy functions	Electronic sorting; multi-job; adjustments (contrast, sharpness,
	image density); proof copy; interrupt mode; colour mode;
	separate scan; sort/group; combination; original selection;
	ID card copy; 2-in1; 4-in-1

PRINTER SPECIFICATIONS

Print resolution	600 x 600 dpi
	1,200 x 1,200 dpi (reduced speed)
Page description	PCL 5e/c Emulation, PCL XL Ver. 3.0 Emulation, PostScript 3
language	Emulation (3016), XPS Ver. 1.0, OpenXPS, PDF 1.7
Operating systems	Windows XP (32/64)
	Windows Vista (32/64)
	Windows 7 (32/64)
	Windows 8 (32/64)
	Windows Server 2003 (32/64)
	Windows Server 2003 R2 (32/64)
	Windows Server 2008 (32/64)
	Windows Server 2008 R2
	Windows Server 2012
	Macintosh OS X Ver. 10.2.8 or later
	Linux
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Print functions	Direct print of TIFF, XPS, PDF and OOXML (DOCX, XLSX, PPTX);
	secure print; combination; n-up; poster; booklet page order;
	watermark

If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed
 Warm-up time may vary depending on the operating environment and usage



SCANNER SPECIFICATIONS

Scan speed (mono/colour)	Up to 35 opm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-eMail
	Scan-to-SMB
	Scan-to-FTP
	Scan-to-HDD
	Scan-to-USB
	Scan-to-WebDAV
	Network TWAIN scan
File formats	JPEG; TIFF; PDF; PDF/A (1b); Compact PDF; XPS
Scan destinations	2,100 (single + group); LDAP support
Scan functions	Up to 400 job programs

FAX SPECIFICATIONS

Fax standard	Super G3 (optional)
Fax transmission	Analogue
	i-Fax
Fax resolution	Max.: 600 x 600 dpi (ultra-fine)
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,100 (single + group)
Fax functions	Time shift; PC-Fax; fax forwarding; up to 400 program dials

SYSTEM FEATURES

	-
Security	ISO 15408 EAL3 (in evaluation); IP filtering and port blocking; SSL2; SSL3 and TSL1.0 network communication; IPsec support; IEEE 802.1x support; user authentication; secure print; hard disk overwrite (8 standard types); hard disk data encryption, copy protection (print only)
Accounting	Up to 1,000 user accounts; Active Directory support
	ID card authentication optional
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	PageScope Mobile

- All specifications refer to A4-size paper of 80 gsm quality.

 The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.

 The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.

 Some of the product literations contain actional accessories.
- Some of the product illustrations contain optional accessories.

 Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.

 Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.























