TASKalfa 2550ci

COMPACT COLOUR MULTIFUNCTIONAL FOR A3 FORMAT

THE COMPACT ALL-ROUNDER FOR COLOUR IN A3

The TASKalfa 2550ci provides highquality A4/A3 colour output and maximum flexibility for workgroups and small offices, whether printing, copying, scanning or faxing. All the functions you need are packed into a compact, reliable and user-friendly device and easily accessible via a large colour touch panel. So no matter how your workflows are organised, you can be more productive with the TASKalfa 2550ci.

- Up to 25/25 pages per minute A4 in b/w and colour
- Advanced colour technology for consistently superb image quality
- Time to first copy: 9.9 seconds in colour
- Up to 2 GB RAM + 160 GB HDD memory and storage
- Standard network colour printing and scanning
- Expandable fax functions: dual fax, network fax and internet fax
- Standard 50-sheet reversing document processor and 30-sheets job separator
- Standard paper capacity of 1,100 sheets expandable up to 2,100 sheets
- Long-life components provide exceptional efficiency and reliability



Easy-to-install hanging finisher with 500 sheets capacity, also supports stapling.

Wide-screen, easyto-use, colour touch panel gives simple, intuitive access to all device functions.









TASKalfa 2550ci COLOUR MULTIFUNCTIONAL FOR A3 FORMAT

The TASKalfa 2550ci corporates extremely durable components that guarantee efficient and reliable operation to meet the demand-TASKalfa 🌮 ing requirements of busy office environments. The TASKalfa 2550ci provides effective productivity and maximum flexibility whilst ensuring minimum impact on the environment.

Technology: KYOCERA Colour Laser, HyPAS solution platform Engine speed (pages per minute) Up to 25/13 ppm A4/A3 in colour and b/w

Resolution 600 x 600 dpi, multi-bit technology for print quality of 9,600 dpi equivalent x 600 dpi

Warm-up time from power on Approx. 45 seconds or less

Time to first page Approx. 7.9 sec. or less in b/w; 9.9 sec. or less in colour

CPU IBM PowerPC 750CL/600 MHz Memory (standard, max.) 2 GB RAM + 160 GB HDD

Standard interface USB 2.0 (Hi-Speed), USB Host 2.0, Fast Ethernet 10BaseT/ 100BaseTX/1000BaseT, slot for optional print server, slot for optional CompactFlash® card, slot for optional fax system

Dimensions (W x D x H) Main unit: 594 x 699 x 862 mm Weight: Main unit + standard DP approx, 95.5 kg

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption Printing: 651 W (in colour, b/w) Ready mode: 145 W Sleep mode: 16 W

Noise (ISO 7779 / ISO 9296) Printing: 63.8 dB(A) in colour, 63 Stand-by (ready mode): 49 dB(A) r, 63.8 dB(A) in b/w

Safety standards: CS, TÜV, CE This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard. RoHs compatibility

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity

100-sheet multi-purpose tray, 60–256 g/m², A6R–A3; 2 x 500-sheet universal paper cassette, 60–256 g/m², A5R–A3 Max. input capacity with options: 2,100 sheets A4

Duplex unit: Duplex as standard supports A5-A3, 60-220 g/m² **Document processor** (reversing): 50-sheet, 45–160 g/m², A5R-A3, folio

Output capacity max. 280 sheets (250 sheets, job separator area 30 sheets)

Controller language: PRESCRIBE

Emulations: PCL6 (PCL5c / PCL-XL), KPDL3 (PostScript 3 com-patible), PDF Direct Print, XPS Direct Print

Operating systems: All current Windows operating systems, Mac OS X Version 10.4 or higher, UNIX LINUX, as well as other operating systems on request

Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)

Print features: Encrypted PDF Direct Print, IPP printing, e-mai printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage and job management functionality e-mail

Your KYOCERA Business Partner:

Max. original size: A3

Continuous copying: 1-999

Zoom range: 25-400% in 1% steps Preset magnification ratios: 5R / 5E

Digital features: Scan-once-copy-many, electronic sort, 2in1 and 4in1 function, image repeat copy, page numbering, cover mode, booklet copy, interrupt copy, form overlay, stamp function

Exposure mode: Auto, manual: 7 or 13 steps

Image adjustments: Text + photo, text, photo, map

Functionality: Scan-to-email, Scan-to-FTP, Scan-to-SMB, Scan-to-USB Host, Scan-to-box, Network TWAIN, WSD scan

Scan speed (A4, 300 dpi, simplex) 48 images per minute in b/w and colour

Scan resolution: 600 dpi, 400 dpi, 300 dpi, 200 dpi, 200 x 100 dpi, 200 x 400 dpi (256 greyscales)

Max. scan size: A3

Original recognition: Text, photo, text + photo

Network protocol: TCP/IP

File types: PDF (high compressive, encrypted, PDF/A), JPEG, TIFF, XPS

Compatibility: ITU-T Super G3

Modem speed: Max. 33.6 kbps

Transmission speed: Max. 3 seconds (JBIG)

Scanning density Normal: 8 dot/mm x 3.85 line/mm Fine: 8 dot/mm x 7.7 line/mm Superfine: 8 dot/mm x 15.4 line/mm Ultrafine: 16 dot/mm x 15.4 line/mm halftone

Max. original size: A3

Compression method: JBIG, MMR, MR, MH

Memory: Standard 12 MB, max. 120 MB

Features: Opt. Internet-fax, network faxing, rotate transmission, rotate reception, duplex fax reception, memory reception, mailbox, remote diagnostics, dual fax with second fax system

Average continuous toner yield in accordance with 5% coverage A4

TK-8315K Toner-Kit: Toner black for 12,000 pages TK-8315C, TK-8315M, TK-8315Y Toner-Kits: Toner cyan, magenta, yellow for 6,000 pages

Staple cartridge SH-10 for DF-470

Fax system (W)

Internet Fax Kit (A)

Paper handling

PF-790 Paper feeder 2 x 500 sheets, 60–256 g/m², A5R-A3

DT-730 Document tray

MM-16-128: Image memory (120 MB)

DF-470* Document finisher + AK-470 Main tray: 500 sheets A4, 60–256 g/m², B5E–A3, 3 positions stapling up to 50 sheets A4 or 25 sheets A3 *Bridge unit AK-470 is required for the use of DF-470.

Memory CompactFlash® card 1 slot (up to 4 GB) for printing forms, fonts, logos, macro storage

Fax memory

Security Data security kit (E)

USB IC Card Reader Card Reader Holder (B) UG-33: ThinPrint support

Optional interface IB-50: Gigabit-Ethernet board 10BaseT/100BaseTX/1000BaseT

CB-790 Wooden cabinet CB-791 Metal cabinet





KYOCERA Document Solutions Europe B.V. – Branch Office Germany – Otto-Hahn-Straße 12 – 40670 Meerbusch – Germany Tel +49 (0) 2159 928-500 – Fax +49 (0) 2159 918-100 www.kyoceradocumentsolutions.eu – info@deu.kyocera.com KYOCERA Document Solutions Inc. – 2-28, 1-Chome – Tamatsukuri – Chuo-Ku Osaka 540-8585 – Japan – www.kyoceradocumentsolutions.com

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

202DS TASKalfa 2550ci EMC