

> PRINT > COPY > SCAN > FAX

TASKalfa 6003i

MONOCHROME MULTIFUNCTIONAL FOR FOR A4/A3 FORMAT





With advanced measures in security and usability, the new TASKalfa 6003i ensures that information is kept under virtual lock and key whilst being easily accessible for users. The use of a touch-screen panel allows for professionals to benefit from easier usability and enhanced flexibility with their documentation. This multifunctional product offers high quality monochrome printing which can be finished with a range of flexible options perfect for any type, format or length of document. An award-winning engine also provides unbeatable reliability and consistency to strengthen its offering as the complete solution to office document requirements.

- > Up to 60/30 pages A4/A3 per minute
- > User friendly and intuitive 10.1 inch operation panel
- > Flexible paper handling from A6 up to SRA3 for up to 7,150 sheets
- > Great range of high speed colour scanners and productive finishing
- > High-level build in security features including data encryption, Trusted Platform Module, Secure Boot and Run Time Integrity Check
- > Increase productivity and save time with the Human Detection Sensor
- > Comprehensive support for all state-of-the-art mobile communications
- > Long-life components providing exceptional efficiency and reliability, and less waste



TASKalfa When handling sensitive documents in your organisation, you must protect your data, so it doesn't fall into the wrong hands. The new TASKalfa 6003i offers you complete security features as standard to safeguard your information.

GENERAL

Technology: KYOCERA TASKalfa Laser Monochrome, HyPAS solution platform **Touch panel size:** 256.5 mm (10.1 inch) full-colour touch panel display, speaker for job notification, 15° - 90° swivel

Engine speed (pages per minute): Up to 60/30 ppm A4/A3 in colour and b/w; Duplex print speed: 60 pages per minute, A4; Duplex copy speed: 60 pages per minute, A4 Resolution: 4800dpi equivalent x 1200dpi (print), 600 x (600 dpi (car) (cap)) 600 dpi (scan/copy)

Warm-up time from power on: Approx. 17 seconds or less Time to fir st print: 3.8 seconds or less Time to fir st copy: 4.1 seconds or less (DP); 3.4 seconds or less (Platen)

CPU: QorlQ T1024 (Dual Core) 1.2GHz Memory (standard max.): 4 GB RAM + 8 GB SSD + 320 GB HDD

Standard interface: Standard interface: USB 3.0 (Super-Speed USB), 4 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec, 802.3az support), optional Wi-Fi (IEEE 802.11b/g/n), 2 eKUIO slots, for optional internal print server or for optional fax system, slot for optional Wireless LAN, Slot

for optional SD Card, NFC tag
Dimensions (W x D x H): Main unit: 602 x 665 x 790 mm
Weight: Main unit: Approx. 83 kg

Power source: AC 220 V ~ 240 V, 50/60 Hz Power consumption: Printing: 878 W

Copying: 878 W Ready mode: 50 W Low power mode: 50 W Sleep mode: 0.7 W

Noise (sound pressure level ISO 7779 measurement distance of 1 meter):

Copying/Printing: 54.9 dB (A) Stand-by: 35 dB (A) **Safety standards:** GS, TÜV, CE.

This unit is manufactured according to ISO 9001 quality

standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions

Input capacity:

input capacity: 150-sheet multipurpose tray, 52 – 300 g/m² (Banner 136 – 163 g/m²), A6R – SRA3 (320 x 450 mm), Custom (98 x 148 to 297 x 457.2 mm), Banner max. 304.8 x 1,220 mm; 2x 500-sheet universal paper cassette, 52 – 300 g/m², Upper cassette A6R up to A4R, lower cassette A6R up to

SRA3,
Max. input capacity with options: 7,150 sheets A4

Duplex unit: Duplex as standard supports
A6R-SRA3, 64-256 g/m²
Output capacity: Standard 500 sheets face-down, max. output capacity 4,300 sheets

PRINT FUNCTIONS

Controller language: PRESCRIBE Emulations: PCL6 (PCL5c / PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and

Operating systems: All current Windows operating systems, Mac OS X Version 10.9 or higher, UNIX LINUX,

as well as other operating systems on request Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of onedimensional barcodes plus two-dimensional barcode

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec,SNMPv3, quick copy, proof and hold, private print, job storage functionality

Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google cloud print

COPY FUNCTIONS

Max. original size: A3 / Ledger Continuous copying: 1 – 9999
Zoom range: 25 – 400% in 1% steps
Preset magnification ratios: 5R/5E,

Digital features: Scan-once-copy-many, electronic sort, 2in1, 4in1, image repeat, page numbering, cover mode, booklet copy, interrupt copy, form overlay, margin shift, auto cassette change, Skip blank page, ID copy **Exposure mode:** Auto, manual: 16 steps **Image adjustments:** Text + photo, text, photo,

Diagram/map

SCAN FUNCTIONS

Functionality: Scan to e-mail, Scan to FTP, Scan to SMB, Scan to USB Host, Scan to box, Network TWAIN, WIA/WSD

Scan speed: 220 images per minute (300 dpi, A4 duplex, with DP-7130) in b/w and colour
Scan resolution: A4 - 600dpi x 600dpi, 400dpi x 400dpi,

Scan resolution: A4 - 60040pt; 8004pt; 4004pt; 4004pt; 2004pt; 4004pt; 3004pt; 2004pt; 2004pt; 2004pt; 2004pt; 256 greyscales per colour

Max. scan size: A3, Ledger

Original recognition: Text, photo, text + photo, Light Text / Fine Line, optimised for OCR

File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted

PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u, Searchable PDF(Option), MS Office file(Option)

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3

Modem speed: Max. 33.6 kbps Transmission speed: Max. 3 seconds (JBIG) Scanning speed: 2.0 seconds or less Address book: 2000 entries

Maximum original size: A3, Banner up to 1,600 mm Compression method: JBIG, MMR, MR, MH

Features: Network faxing, rotate transmission rotate reception, encrypted transmission and reception, duplex fax reception, memory reception, mailbox, remote diagnostics, polling transmission and reception, broadcast, Optional Internet-fax, dual fax with second fax

CONSUMABLES

Average continuous toner yield in accordance with 6% coverage A4.

TK-6325 Toner-Kit: Toner black for 35,000 pages A4 sheets (in accordance with 6% coverage b/w:colour = 7:3)

Staple cartridge: SH-10 5000 x 3 staples, for DF-7100, DF-7120, BF-730 and BF-9100

SH-12 5000 x 3 staples, for DF-7110 **SH-14** 5000 x 5 staples, for DF-7130

Fax System 12 Internet Fax Kit (A)

Scan Extension Kit (A):
Scan to searchable PDF solution (embedded OCR), convert to PDF or MS Office(docx,xlsx,pptx)

Paper handling

DP-7100 Document processor: (Reversing), 140 sheets, 35 – 160 g/m² (simplex), 50–120 g/m² (duplex), A6R – A3 Banner up to 1,900 mm

DP-7110 Document processor: (one-path duplex scanning) 270 sheets at 50 - 80 g/m², 35 - 220 g/m² (simplex), 50 - 220 g/m² (duplex), A6R - A3 Banner up to 1,900 mm

DP-7130 Document processor: (one-path duplex scanning with ultrasonic sensor), 270 sheets at 50-80 g/m², 35-220 g/m² (simplex), 50-220 g/m² (duplex), A6R-A3, Banner up to 1,900 mm

DT-730(B) Document tray PF-7100 Paper feeder: 2x 500 sheets, 52 – 300 g/m²,

PF-7110 Paper feeder: 2x 1,500 sheets, 52 - 300 g/m², A4,

PF-7120 A4 side Deck: 3,000 sheets, 60 - 300 g/m², A4, B5 **DF-7100 Inner finisher:** Main tray: 500 sheets A4, 52–300 g/m², A6R–SRA3

DF-7110* Document finisher + AK-7110:

Main tray: Max. 4,000 sheets A4; max. 52 – 300 g/m²; max. A6R – SRA3 Sub tray: 200 sheets A4; 52 – 300 g/m²; A6R – SRA3

Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions, B5 – SRA3

DF-7120' Document finisher + AK-7110:
Main tray: 1,000 sheets A4, 52 – 300 g/m², A6R – SRA3,
Stapling up to 50 sheets A4 or 30 sheets A3 at 3 position
DF-7130' Document finisher + AK-7110: Main tray: 4,000 sheets A4; Sub tray: 200 sheets 52–300 g/m² A6R–SRA3 Stapling up to 100 sheets A4 or 50 sheets A3 at 3 posi-

AM:7110 Attachment kit for DF-7110, DF-7120 and DF-7130: 100 sheets, 52–300 g/m², AGR-SRA3, * Bridge unit AK-7110 is required when using a finisher PH-7C/PH-7D Punch unit for DF-7110/DF-7120/ DF-7130:

PH-7C/PH-7D Punch unit for DF-7110/DF-7120/ DF-7130: 2-hole/4-hole/Swedish type, 60 – 256 g/m², ASR – A3 MT-730(B) Mailbox sorter for DF-7110: 7 bins x 100 sheets A4, 50 sheets A3/B4, 60 – 163 g/m² BF-730 Booklet and tri-folding unit for DF-7110 Half-folding: 52–256 g/m², A3, B4, A4R Booklet: Max. 16 sheets (64 pages, 60–90 g/m²) Non-staple folding: Max. 5 sheets (60–90 g/m²) Tri-folding: 60–105 g/m², A4R Multi tri-folding: 5 sheets (60–90 g/m²), 3 sheets (91–105 g/m²)

(91-105 g/m²)

BF-9100 Booklet and tri-folding unit for DF-7130

Half-folding: 52-256 g/m², A3, B4, A4R Booklet: Max 20 sheets (80 pages, 60-90g/m²) or Max 13 sheets(52 pages 91-105g/m²) Non-staple: Max 5 sheets(60-90g/m²) or Max 3 sheets(91-105g/m²)

Tri folding: Max 5 sheets(60-90g/m²) or Max 3 sheets(91-105g/m²)

JS-7100 Job separator:

100-sheet internal job separator, 52 – 300 g/m², ASR – SRA3 PH-7120: Inner punch unit for DF-7100 inner finisher PH-7130: Inner punch unit for DF-7100 inner finisher/

Swedish type Banner Guide 10: Banner paper feeding guide, 10 sheets
Keybordholder 10

NK-7120 Numeric keypad
USB IC Card Reader + Card Authentication Kit (B):
Support for various authentication keys available.

The card holder is standard

UG-33 AC: ThinPrint support

UG-34 AC: Emulation (IBM Proprinter/EPSON LQ-850/ Diablo 630)

Optional interface IB-35: Direct Wi-Fi Interface

IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/ 1.000 BaseT

IB-51: Wireless LAN Interface (802.11b/g/n)

Platen cover (E) CB-7100W: Wooden cabinet CB-7110M: Metal cabinet

















2132NP Hoofddorp - The Netherlands

Tel +31 (0)20 6540 000 - Fax +31(0)20 653 1256 www.kyoceradocumentsolutions.eu - info@deu.kyocera.com

KYOCERA Document Solutions Inc. - 2-28, 1-Chome - Tamatsukuri Chuo-Ku - Osaka 540-8585 - Japan - www.kyoceradocumentsolutions.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

