TASKalfa 6550ci

COLOUR MULTIFUNCTIONAL FOR A3 FORMAT

NEED THE BEST COLOUR QUALITY FROM A FAST AND RELIABLE MULTIFUNCTIONAL? Fast, efficient, productive and reliable: this is the new TASKalfa 6550ci multifunctional device. With its optimised imageprocessing engine, you're guaranteed truly outstanding colour print and image quality. Add that to a standard 4,150 sheet capacity, expandable to 7,650 sheets, and this new multifunctional device comes equipped to handle even the heaviest of office workloads.

- Up to 65 pages per minute A4 in colour
- Advanced colour technology for excellent quality
- Standard network colour high-speed printing and scanning
- Optional EFI Fiery controller and colour management
- 2 GB RAM and big storage capacity of 320 GB HDD
- ▶ Wide range of media up to 300 g/m², 304.8 x 457.2 mm and banner printing
- Standard 4,150-sheet paper capacity, expandable to 7,650 sheets
- Expandable fax functions: dual fax, network fax, and internet fax
- Enhanced security functions: Optional Data Security Kit, Copy Guard Kit, USB IC Card Reader
- Long-life components provide unprecedented efficiency and reliability



The colour touch panel with large, easily understandable icons offers simple, straightforward operation.

Choose the sidedeck paper feeder cassette to provide high volumes of paper to suit your high-volume print projects.









The TASKalfa 6550ci corporates extremely durable components that guarantee efficient and reliable operation to meet the demanding requirements of busy office environments. demanding requirements of busy office environments. The TASKalfa 6550ci provides effective productivity and maximum flexibility whilst ensuring minimum impact on the environment.

General

Technology KYOCERA Laser Colour, HyPAS[™] solution platform Engine speed (pages per minute) Up to 65/32 A4/A3 in colour and in b/w

Resolution

600 x 600 dpi, Multi-bit technology for print quality of 9,600 dpi equivalent x 600 dpi

Warm-up time from power on Approx. 60 seconds or less

Time to first page Approx. 5.4 sec. or less in b/w: 6.2 sec. or less in colour

CPU IBM PowerPC 750GL/916 MHz

Memory 2 GB RAM + 320 GB HDD

Standard interfaces

USB 2.0 (Hi-Speed), USB Host 2.0, Fast Ethernet 10Base- T/ 100BaseTX/1000BaseT, slot for optional print server, slot for optional CompactFlash® card, slot for optional fax system

Dimensions (W x D x H) - main unit 685 x 801 x 1,053 mm (DP, operation panel not included) 1,039 x 801 x 1,347 mm (DP, operation panel included) Weight: Main unit approx. 183 kg

Power source: AC 220 V ~ 240 V. 50/60 Hz

Power consumption Printing: 1,570 W (in colour), 1,420 W (in b/w) Ready mode: 330 W Sleep mode: 23 W

Noise (sound pressure level ISO 7779/ISO 9296) Printing: b/w 53.6 dB(A) LpA / colour 53.9 dB(A) LpA Stand-by: 35.4 dB(A) LpA

Safety standards: GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard. RoHs compatibility

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity

Input capacity 150-sheet multi-purpose tray, 60-300 g/m² (banner 136-163 g/m²), A6R-304.8 x 457.2 mm, banner max. 304.8 x 1,219.2 mm; 2 x 1,500-sheet high-capacity paper deck, 60-256 g/m², A4, B5 2 x 500-sheet universal paper cassette, 60-256 g/m², A5R-304.8 x 457.2 mm

Max. input capacity with options: 7,650 sheets A4

Document processor (one-path duplex scanning) 270 sheets; 35–220 g/m² (simplex), 50–220 g/m² (duplex); A5R–A3 Duplex unit: Duplex as standard supports A5R-304.8 x 457.2 mm, 60-256 g/m²

Output capacity Max. 420 sheets (standard job separator tray 70 sheets, Copy tray (D) - optional: upper 100 sheets, lower 250 sheets)

Controller language: PRESCRIBE IIc

Emulations: PCL6 (PCL5c/PCL-XL), KPDL3 (PostScript 3 com-patible), PDF Direct Print, XPS Direct Print

Operating systems: All current Windows operating systems, Mac OS X Version 10.4 or higher, UNIX LINUX, as well as other operating systems on request.

Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, Quick copy, proof and hold, Private Print, job storage and job management functionality

Max. original size: A3

Continuous copying: 1-9,999

Zoom range: 25-400% in 1% steps

Preset magnification ratios: 5R/5E

Digital features: Scan-once-copy-many, electronic sort, 2in1 and 4in1 function, image repeat copy, page numbering, cover mode, booklet copy, interrupt copy, form overlay

Exposure mode: Auto, manual: 7 or 13 steps

Image adjustments: Text + photo, text, photo, map

Functionality: Scan-to-email, Scan-to-FTP, Scan-to-SMB, Scan-to-USB Host, Scan-to-box, Network TWAIN, WSD scan

Scan speed (A4, 300 dpi, Dual Scan) b/w 200 images per minute, colour 150 images per minute

Scan resolution: 600 dpi, 400 dpi, 300 dpi, 200 dpi, 200 x 100 dpi, 200 x 400 dpi, (256 greyscales)

Max. scan size: A3

Original recognition: Text, photo, text + photo, optimized for OCR Network protocol: TCP/IP

File types: PDF (high compressive, encrypted, PDF/A), JPEG, TIFF, XPS

Compatibility: ITU-T Super G3 Modem speed: Max. 33.6 kbps

Transmission speed: Max. 3 seconds (JBIG)

Scanning density Normal: 8 dot/mm x 3.85 line/mm Fine: 8 dot/mm x 7.7 line/mm Superfine: 8 dot/mm x 15.4 line/mm Ultrafine: 16 dot/mm x 15.4 line/mm halftone

Max. original size: A3

Compression method: JBIG, MMR, MR, MH Memory: Standard 12 MB, max. 120 MB

Features: Opt. Internet-fax, network faxing, rotate transmission, rotate reception, duplex fax reception, memory reception, mailbox, remote diagnostics, dual fax with second fax system

Average continuous toner yield in accordance with 5% coverage A4.

TK-8705K Toner-Kit: Toner Black for 70,000 pages TK-8705C, TK-8705M, TK-8705Y Toner-Kits: Toner Cyan, Magenta, Yellow for 30,000 pages

WT-861 Waste Toner Bottle

150.000 sheets (in accordance with 5% coverage. Colour/Mono = 6:4) Staple cartridge: SH-10 for BF-730, SH-12 for DF-790

Fax System (V) Internet Fax Kit (A)

Printing System (12): Fiery Controller

Printing System Interface Kit (A): Interface board for Fiery

Paper handling

PF-730 Paper feeder 2 x 500 sheets, 60–256 g/m², A5R–304.8 x 457.2 mm, folio

PF-740 Paper feeder 3,000 sheets, 60–256 g/m², A4, B5, letter

PF-770 A4 side deck 3,000 sheets, 60–300 g/m², A4, B5 **PF-780 Multimedia tray and paper path unit** 500 sheets, 60–256 g/m², A5R–304.8 x 457.2 mm **DF-790 Document finisher**

Main tray: max. 4,000 sheets A4 (3,000 sheets with attachment BF-730); max. 60-300 g/m²; max. B5R-304.8 x 457.2 mm Sub tray: 200 sheets A4; 60-300 g/m²; A6R-A3 Sub tray (top): 100 sheets; 60-300 g/m²; A6R-A4 Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions, B5-304.8 x 457.2 mm

PH-7C/PH-7D Punch unit for DF-790 2-hole/4-hole/Swedish type, 60-300 g/m², A5R-A3

MT-730 Mailbox sorter for DF-790 7 bins x 100 sheets A4, 50 sheets A3/B4, 60-163 g/m²

BF-730 Booklet and tri-folding unit for DF-790

BF-730 BOOKlet and tri-folding unit for DF-790 Half folding: 60–256 g/m², A3, B4, A4R Booklet: max. 16 sheets (64 pages, 60–90g/m²) Non-staple folding: max. 5 sheets (60–90g/m²) Tri-folding: 60–120 g/m², A4R Multi tri-folding: 5 sheets (60–90g/m²), 3 sheets (91–120g/m²)

Banner Guide (A) Banner paper feeding guide, up to 10 sheets

Memory

CompactFlash[®] card 1 slot (up to 4 GB) for printing forms, fonts, logos, macro storage Fax memory

MM-16-128: Image memory (120 MB)

Security

Data security kit (E) ISO 15408 (Common Criteria) with security level EAL3

Printed Document Guard Kit (A)

USB IC Card Reader UG-33: ThinPrint support

UG-34: Emulation (IBM Proprinter/EPSON LQ-850/Diablo 630) **Optional interface**

IB-50: Gigabit-Ethernet board 10BaseT/100BaseTX/1000BaseT

Copy tray (D): Sub upper 100 sheets, lower 250 sheets





Your KYOCERA Business Partner:



KYOCERA Document Solutions Inc. – 2-28, 1-Chome – Tamatsukuri – Chuo-Ku Osaka 540-8585 – Japan – www.kyoceradocumentsolutions.com

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

Document Solutions