

Your new Security Officer.

P-4532i MFP · P-4539i MFP P-5539i MFP · P-6039i MFP

The A4 multifunctional systems are now free of data security limitations. In addition to a print resolution of 1,200 x 1,200 dpi and a high output speed of up to 60 A4 pages per minute, the P-4532i MFP, P-4539i MFP, P-5539i MFP and P-6039i MFP also offer comprehensive data security functions that are otherwise only seen in A3 systems. And their intuitive colour touch screens are designed for groundbreakingly easy and convenient operation. All this means you now get security and convenient operation rolled into one compact format.

What you can expect:

PERFECTLY SECURED: The integrated Data Security Kit featured in these MFPs guarantees the security of your data in accordance with the current applicable ISO requirements. In addition, the USB card reader*, which enables you to identify yourself in the system using a chipcard or transponder without contact, also offers highly effective security. But that's not all: the Secure Boot procedure, when starting the system, and the Run-Time Integrity Check, when the system is running, ensure that authorised firmware is used and thereby protect your data, both now and in the future.

EXTREMELY EFFICIENT: With the MultiCrop Scan HyPAS app, the laborious task of scanning in receipts one by one can now be done quickly and easily. In just one step, multiple receipts can be digitally cut, straightened and scanned in one operation and stored separately as a file. Dual-scan feed is available for professional and extensive digitalisation. In the P-6039i MFPs, this feature is additionally equipped with an ultrasonic sensor that stops the scanning process in situations such as when two or more originals are fed in at once. This way, none of your valuable data gets lost.

100% INTUITIVE: The adjustable, 7 inch touch panel guarantees the unparalleled user-friendliness of these A4 systems. The standard HyPAS™ interface for integrating optional customer-specific software solutions and applications as well as the optional Scan Extension Kit for automatically creating text-searchable PDF files are two more features that help bring innovation and efficiency to your work.

HIGHLY PRODUCTIVE: Thanks to a printing speed of 45, 55 or 60 A4 pages per minute and a huge paper capacity of up to 2,600 sheets, getting big jobs done quickly and avoiding unnecessary waiting times is a breeze. Moreover, mobile printing and scanning via the free Mobile Print app and printing via Apple AirPrint* or Wi-Fi* will quickly make these versatile all-in-one systems irreplaceable 'colleagues' in your office.



P-4532i MFP · P-4539i MFP P-5539i MFP · P-6039i MFP Digital Multifunctional System Copy / Print / Scan / Fax

Technical Data

Technical Data:

P-4532i MFP · P-4539i MFP · P-5539i MFP · P-6039i MFP

Type

P-4532i MFP: Copy, print, scan Function

P-4539i MEP/P-5539i MEP/P-6039i MEP Copy, print, scan, fax

Print technology Laser b/w

max A4 from platen glass Original format

Original feeder P-4532i/P-4539i MFP:

75 sheet document processor with automatic reverse function, A6R-A4, 50-120 g/m² (standard)

P-5539i/P-6039i* MFP:

100 sheet document processor with simultaneous duplex scanning and *double feed prevention sensor, A6R-A4, 50-120 g/m² (standard)

Copy/print speed

P-4532i/P-4539i MFP: max 45 A4 pages/ min, duplex: max 22.5 A4 pages/min P-5536i MFP: max 55 A4 pages/min,

duplex: max 39.5 A4 pages/min P-6036i MFP: max 60 A4 pages/min, duplex: max 43 A4 pages/min

1st page (print/copy)*

5.3/6 seconds (P-4532i/P-4539i MFP) 4.5/6 seconds (P-5539i/P-6039i MFP)

23 seconds (P-4532i/P-4539i MFP) / 25 seconds (P-5539i/P-6039i MFP) Warm-up time

Copy resolution 600 x 600 dpi Greyscales

P-4532i/P-4539i MFP: 1 x 500 sheet Paper feed

universal cassette (A5R-A4, min 140 x 210 mm, max 216 x 356 mm) P-5539i/P-6039i MFP: 1 x 500 sheet

r-353/Jr-6033/Jr-6033/Mr-1. Z500 Sitest universal cassette (A6R-A4, min 105 x 148 mm, max 216 x 356 mm); 100 sheet multi-bypass (A6R-A4 [min 70 x 139.7 mm, max 216 x 356 mm]), banner length: max 915 mm

Universal cassette 60-120 g/m², Paper weights

multi-bypass 60-220 g/m², duplex 60-120 g/m²

P-4532i/P-4539i MFP: Paper output 250 sheet A4 (face-down)

P-5539i/P-6039i MFP: 500 sheet A4 (face-down), 250 sheet A4 (face-up with optional PT-320)

1.5 GB RAM, (max 3.5 GB RAM), 64/256/512 GB SSD** System memory

1-999 copies

Continuous copying

25 %-400 % in steps of 1 %

Zoom Functions

Colour touch screen (7 inch), duplex, job reservation, favourites (programs), ID card copy, scan once - copy many, continuous scan, skip blank pages, N-up, quiet mode (half speed mode), 100 management codes, Data Security

Kit, Secure Boot, Runtime Integrity Check, etc.

DIMENSIONS/WEIGHT

P-4532i/P-4539i MFP: **Dimensions** 575 x 475 x 476 mm (H x W x D)

P-5539i MFP:

590 x 480 x 495 mm (H x W x D),

P-6039i MFP: 610 x 480 x 495 mm (H x W x D)

P-4532i/P-4539i MFP: approx. 22.5 kg, Weight

P-5539i MFP: 24.1/P-6039i MFP:

approx. 24.5 kg

ENVIRONMENT

Mains voltage 220/240 V, 50/60 Hz

Power consumption

P-4532i/P-4539i MFP: approx. 1,270 W max, approx. 599/564 W in operation, approx. 57/56 W in stand-by mode, approx. 0.5 W in sleep mode, TEC value: 0.62 KWh/week

P-5539i MFP/P-6039i MFP: approx 1,287/1,309 W max, approx. 704/741 W in operation, approx. 60/58 W in stand-by mode, approx. 0.6/0.5 W in sleep mode, TEC value: 0.78/0.84 KWh/week

Noise level

P-4532 MFP/P-4539 MFP: approx. 52.6 dB(A) in operation approx. 22.0 dB(A) in stand-by mode (DIN ISO 7779/9296)

P-5539i MFP/P-6039i MFP: appox. 54.5/56.0 dB(A) in operation, appox. 23.3/22.7 dB(A) in stand-by mode (DIN ISO 7779/9296)

GS/TÜV, CE Safety

PRINT SYSTEM

Туре Integrated within the system

Print format A6R-A4

Print resolution 1,200 x 1,200 dpi

ARM Cortex-A53 Dual Core, 1.4 GHz Processor USB 2.0, 10/100/1000BaseTX, USB host Interfaces

Network protocols TCP/IP. Net BEUI

Windows 8/8.1/10/11. Server 2012/2012 Operating R2/2016/2019/2022, Linux, Chrome OS,

Mac ex OS 10.14

Emulations

PCL6 (PCL 5e/c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, XPS,

Open XPS, PDF 1.7

Functions

USB direct printing, printing of e-mails, proof & hold, private printing, barcode printing, WSD/internet printing; Mobile Print/Apple AirPrint**, Wi-Fi**, Microsoft Universal Print

Scan type CCD colour and b/w

Scan format max A4

P-4532i/P-4539i MFP: b/w: max 60/26 A4 originals/min (simplex/duplex) with 300 dpi, colour: max 40/17 A4 originals/min (simplex/duplex) with 300 dpi

P-5539i MFP/P-6039i MFP: b/w: max 60/ 120 A4 originals/min (simplex/duplex) with 300 dpi, colour: max 40/80 A4 originals/min (simplex/duplex) with 300 dpi

Scan resolution 200 dpi, 300 dpi, 400 dpi, 600 dpi

Photo, text, photo/text, optimised for OCR

File types

TIFF, JPEG, PDF, PDF/A-1a, PDF/A-1b, PDF/A-2a, PDF/A-2b, PDF/A-2u, high compression PDF, encrypted PDF, XPS, Open XPS, MS Office/text-searchable PDF**

Interfaces 10/100/1000BaseTX, USB 2.0

TCP/IP Network protocol

Windows 8/8.1/10/11, Server 2012/2012 Operating systems

R2/2016/2019/2022

Scan to SMB, Scan to e-mail, Scan to FTP, Scan to USB, TWAIN scan, WIA scan, **Functions**

SMTP authentication, LDAP, Multi Crop function***

FAX SYSTEM (P-4539i MFP - P-5539i MFP - P-6039i MFP)

Compatibility Super G3 Original format max A4 Modem speed 33.6 kbps

Transmission

3 seconds or less using JBIG

Compression method

JBIG, MMR, MR, MH

Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi) Fax resolution

Fax memory 8 MB (3.5 MB image memory)

Abbreviated dial 200 numbers One touch dial 100 numbers 50 numbers Group dial

Operating Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016

Network fax driver, automatic redialling, Functions

delayed transmission

OPTIONS

max 4 x PF-3110 (500 sheet universal cassettes [A5R-A4, 60-120 g/m²]) Paper feed

Other options

PT-320 output tray (250 sheet face-up, only for P-5539i MFP/P-6039i MFP), Scan Extension Kit (A)***, Card Authentication Kit (B), Card Reader Holder (10), UG-33 Module), IB-50 Gigabit Ethernet card, IB-37 (5 GHz) or IB-38 (2.4 GHz)**** WLAN card, HD-17 SSD (64 GB), HD-18 SSD (256 GB), HD-19 SSD (512 GB), MM-20 (1 GB DIMM), MM-21 (2 GB DIMM), MS-5100 B manual stapler for 20 sheet (only for P-5539i MFP/P-6039i MFP), cabinet no.

79 (high), cabinet no. 80 (low), CA-3100

depending on operating status

optional

additional memory required **** country specific











TA Triumph-Adler is the document business expert. We offer our clients individual analysis, consultancy and efficient document workflows - not only on paper, but also electronically and with long-term service. For whenever professional users manage, print, photocopy, fax, present or archive documents, or need to optimise processes, TA Triumph-Adler concepts and solutions are the first choice. Our customers benefit greatly from the user-optimised technologies offered by our innovative systems. TA Triumph-Adler and the TA Triumph-Adler logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names are the registered trademarks of their respective owners.

TA Triumph-Adler



triumph-adler.com